

Product Identification: Southern Yellow Pine Wood Chips

SYNONYM: SYP Sawdust; sawdust

CAS No.: None

PRODUCT DESCRIPTION:

Wood chips generated during the processing of southern yellow pine wood products composed of wood particles of varying sizes.

HAZARD INFORMATION:

This product does not present hazards requiring the preparation of a material safety data sheet unless it is utilized in a manner that creates **wood dust**. This **wood dust** and the product itself may exhibit certain health or physical hazards as described in this Material Safety Data Sheet.

SARA TITLE III INFORMATION:

The wood chips are not subject to any current reporting requirements of SARA Title III, Sections 304, 311/312, or 313. If **wood dust** is accumulated in quantities exceeding the regulatory threshold (generally 10,000 pounds), inventory reports under Section 311/312 would be required for that **wood dust**.

PHYSICAL DATA:

Boiling Point	Not Applicable
Specific Gravity	Approximately 0.5 (dry)
Vapor Density	Not Applicable
% Volatile By Vol.	Not Applicable
Melting Point	Not Applicable
Solubility in H ₂ O (% by Wt)	Not Applicable
Evaporation Rate (Butyl Acetate = 1)	Not Applicable

Product Identification: Southern Yellow Pine Wood Chips

pH Not Applicable

Appearance and Odor Light to dark colored wood or granular particles. Color is dependent on age and weathering. May exhibit slight pine odor.

FIRE AND EXPLOSION DATA:

Flash Point Not Applicable

Autoignition Temperature Variable (typically 400 - 500°F)

Explosive Limits in Air 40 grams/m³ (LEL)

Extinguishing Media Water, CO₂, Sand

Special Fire Fighting Procedures Use water to wet down wood chips to reduce the likelihood of ignition or dispersion of dust into the air. Remove the burned or wet residuals to an open area after fire is extinguished.

Unusual Fire and Explosion Hazard Wood dust is a strong to severe explosion hazard if a dust “cloud” contacts an ignition source.

Product Identification: Southern Yellow Pine Wood Chips

HEALTH EFFECTS INFORMATION:

Exposure Limit	(Wood Dust) ACGIH TLV ¹ : TWA - 5.0 mg/m ³ ; STEL (15 min.) - 10 mg/m ³ (softwood)
¹ See footnote below concerning OSHA PEL: OSHA PELs for wood dust	TWA - 15.0 mg/m ³ (total dust); 5.0 mg/m ³ (respirable fraction)
Skin and Eye Contact	Wood dust can cause eye irritation. Various species of wood dust can elicit allergic contact dermatitis in sensitized individuals.
Ingestion	Not Applicable
Skin Absorption	Not Known to Occur
Inhalation	Wood dust may cause nasal dryness, irritation and obstruction. Coughing, wheezing, and sneezing, sinusitis and prolonged colds have also been reported.

¹ In AFL-CIO v. OSHA 965 F. 2d 962 (11th Cir. 1992), the court overturned OSHA's 1989 Air Contaminants Rule, including the specific PELs for wood dust that OSHA had established at that time. The 1989 PELs were: TWA - 5.0 mg/m³; STEL (15 min.) - 10.0 mg/m³ (All soft and hard woods, except western red cedar); Western red cedar: TWA - 2.5 mg/m³.

Wood dust is now officially regulated as an organic dust under the Particulates Not Otherwise Regulated (PNOR) or Inert or Nuisance Dust categories as PELs noted under Health Effects Information section of this MSDS. However, a number of states have incorporated provisions of the 1989 standard in their state plans. Additionally, OSHA has announced that it may cite companies under the OSH Act general duty clause under appropriate circumstances for non-compliance with the 1989 PELs.

Product Identification: Southern Yellow Pine Wood Chips

Chronic Effects **Wood dust**, depending on species, may cause dermatitis on prolonged, repetitive contact; may cause respiratory sensitization and/or irritation. IARC classifies **wood dust** as a carcinogen to humans (Group 1). This classification is based primarily on IARC's evaluation of increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with exposure to **wood dust**. IARC did not find sufficient evidence to associate cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon or rectum with exposure to **wood dust**.

REACTIVITY DATA:

Conditions Contributing to Instability Stable under normal conditions.

Incompatibility Avoid contact with oxidizing agents and drying oils. Avoid open flame. Product may ignite at temperatures in excess of 400°F.

Hazardous Decomposition Products Thermal oxidative degradation of wood produces irritating and toxic fumes and gases, including CO, aldehydes and organic acids.

Conditions Contributing to Polymerization Not Applicable

Product Identification: Southern Yellow Pine Wood Chips

PRECAUTIONS AND SAFE HANDLING:

Avoid eye contact.

Avoid repeated or prolonged contact with skin. Careful bathing and clean clothes are indicated after exposure.

Avoid prolonged or repeated breathing of wood dust in the air.

Avoid contact with oxidizing agents and drying oils.

Avoid open flame.

GENERALLY APPLICABLE CONTROL MEASURES:

Ventilation: Provide adequate general and local exhaust ventilation to maintain healthful working conditions.

PPE: Wear goggles or safety glasses. Other protective equipment such as gloves and approved dust respirators may be needed depending upon dust conditions.

EMERGENCY AND FIRST AID PROCEDURES:

Eyes Flush with water to remove dust particles. If irritation persists, get medical attention.

Skin If a rash or persistent irritation or dermatitis occur, get medical advice where applicable before returning to work where wood dust is present.

Inhalation Remove to fresh air. If persistent irritation, severe coughing, or breathing difficulties occur, get medical advice before returning to work where wood dust is present.

Ingestion Not Applicable

Hood Industries, Inc.
15 Professional Parkway
Hattiesburg, MS 39402
Contact: Director of Engineering
(601) 264-2962

Material Safety Data Sheet
March 31, 2010

Page 6 of 6

Product Identification: Southern Yellow Pine Wood Chips

SPILL/LEAK CLEAN UP PROCEDURES:

Sweep or vacuum spills of wood dust for recovery or disposal; avoid creating dust conditions. Provide good ventilation where dust conditions occur. Place recovered wood dust in a container for proper disposal.

IMPORTANT: The information and data contained herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for your consideration, investigation, and verification. Hood Industries, Inc. makes no warranty of any kind, express or implied, concerning the accuracy or completeness of the information and data herein. Hood Industries, Inc., will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete, or otherwise misleading.